



# For swing gates with leaves up to 4 m, underground installation.

Irreversible electromechanical gear motor 24 Vdc. with magnetic encoder and mechanical stop.



Ideal for intensive use and quick manoeuvres: 90° opening in about 6\* seconds.

Foundation boxes with mechanical stop on opening:

- in stainless steel (LFABBOX4I), ideal for use in extreme conditions,
- with cataphoresis paint finish (LFABBOX4), highly resistant to corrosion.

Maximum freedom of choice: release from inside or outside, lever operated models, freely combinable and easy to operate with just one hand.

Simple installation: built-in mechanical stop system on closure. Standard opening to 110°, or optional 360°.

# Ideal for intensive use. LFAB4024HS is compatible with the control unit Moonclever MC824H. with BlueBUS technology, Solemyo and Opera systems:

- simple programming via a single key:
- · self-learning of travel limits on opening and closing;
- self-diagnostics of faults;
- programming of pause time;
- pass door;
- · deceleration on opening and closing;
- dual technology obstacle detection;
- operation in the event of a power failure with optional rechargeable batteries (PS324);
- provision for connection of latest generation sensitive edges.
- \* Considering standard installation, excluding acceleration and deceleration.



### ACCESSORY FOR L-FAB HS

### BMA2

ADAPTORS FOR A DUAL MOTOR AUTOMATION, COMPATIBLE WITH THE MAJORITY OF FOUNDATION BOXES ON THE MARKET.

PC/PACK, 4



CODE	DESCRIPTION	PACK/PALLET
LFAB4024HS	IRREVERSIBLE 24 Vdc, FAST, WITH MAGNETIC ENCODER AND MECHANICAL STOP ON CLOSING	18
LFABBOX4	FOUNDATION BOX WITH CATAPHORESIS PAINT FINISH FOR LFAB4000, LFAB4024, LFAB4024HS	18
	WITH BUILT-IN MECHANICAL STOP ON OPENING. COMPLETE WITH LEAF COUPLING LEVER	
LFABBOX4I	STAINLESS STEEL FOUNDATION BOX FOR LFAB4000, LFAB4024, LFAB4024HS WITH BUILT-IN MECHANICAL STOP ON OPENING. COMPLETE WITH LEAF COUPLING LEVER	18

### TECHNICAL SPECIFICATIONS

CODE	LFAB4024HS							
ELECTRICAL DATA								
POWER SUPPLY (Vdc)	24							
ABSORPTION (A)	7							
POWER (W)	170							
PERFORMANCE DATA								
SPEED (rpm)	>> 3 <<							
TORQUE (Nm)	200							
WORK CYCLE (CYCLES/HOUR)**	50							
DIMENSIONAL AND GENERAL DATA								
PROTECTION LEVEL (IP)	67							
WORKING TEMP. (°C MIN/MAX)	-20 ÷ +55							
DIMENSIONS (mm)*	375x225x110 h							
WEIGHT (kg)	12.5							


<sup>\*</sup>With foundation box, \*\*The indicated value has to be halved if the opening is up to 180° - by using the BMA1 accessory.

FOUNDATION BOX	LFABBOX4
WEIGHT (kg)	14.4

**DIMENSIONS** 

# UTILISATION LIMITS


# LFAB4024HS



# MAX. GATE LENGTH (M)

Mice · 01 Nice

The shape, the height of the gate and the weather conditions can considerably reduce the values shown in the graph to the side.





BMA3 LEVER-TYPE KEY UNLOCK SYSTEM PC/PACK 1

**ACCESSORIES** 



MEA5 LEVER-TYPE UNLOCK KEY FOR MEA3. PC/PACK 4



BMA1 ACCESSORY FOR OPENING UP TO 360° FOR GATES MAX. 3.5 M IN LENGTH. PC/PACK 1



PLA10 VERTICAL 12 V ELECTRIC LOCK (REQUIRED FOR GATES LONGER THAN 3 m).

PC/PACK 1



PLA11 HORIZONTAL 12 V ELECTRIC LOCK (REQUIRED FOR GATES LONGER THAN 3 m).

PC/PACK 1



TS SIGNBOARD. PC/PACK 1

### COMPATIBILITY TABLE WITH CONTROL SYSTEMS AND ACCESSORIES

	CONTROL UNIT / RECEIVER									TRANSMITTER				PHOTOCELLS									FLASHING LIGHT							
CODE	A01 / Built-in*	A02 / Built-in*	A6F / FLOXI2R*	A700F / FLOXI2R*	A60 / 0XI-SMXI*	A500 / FLOXI2R*	A924 / FLOXI2R*	MC424L / 0XI	MC824H / 0XI	MC824HR / 0XI	ERA INTI	ERA ONE	ERA FLOR	NICEWAY	EPS	EPM	EPL	EPSB	EPMB	EPLB	F210	FT210	F210B	FT210B	급	EL24	ELB	WLT	ELDC	ELAC
LFAB4024HS									•		•	•	•	•				•	•	•			•				•	•	•	

\*Radio receiver incompatible with Opera system



PS324 24 V BATTERY WITH INTEGRATED BATTERY CHARGER.

PC/PACK 1




SOLEMYO KIT THE SOLAR POWER TO AUTOMATE GATES, GARAGE DOORS OR BARRIER GATES.



IT4WIFI
SMART WI-FI INTERFACE
TO CONTROL GATES AND
GARAGE DOORS
VIA SMARTPHONE\*

\*Not compatible with Solemyo Kit and PS324





# NICE, EASY SOLUTIONS FOR HOME AND BUILDING.

SYSTEMS FOR THE AUTOMATION AND CONTROL OF GATES, GARAGE DOORS, BLINDS, SHUTTERS AND ALARM SYSTEMS, WITH INTEGRATED MANAGEMENT USING SMART AND INTUITIVE INTERFACES: PRACTICAL, FUNCTIONAL AND ELEGANT SOLUTIONS TO HELP YOU ENJOY YOUR LIVING SPACES TO THE FULL.



